



## VSP 60HP

Vehicle Mounted Thom-Katt® Pump

## Driven to perform

Now added to our Vehicle-Series product line with the VSP 60HP Vehicle Mounted Thom-Katt\* Pump. It doesn't require a CDL to operate, which means more versatility for your staff.

It delivers the same high-level performance and output as the reliable Thom-Katt TK 60HP on a rugged flatbed-style chassis. The VSP 60HP is well suited for pumping grout, block fill, and shotcrete applications due to its ø6" (150mm) concrete cylinders.

## Standard features

- Large side decks with folding side panels
- Entry steps to both deck sides
- Large side-mounted aluminum toolbox
- 150 gal (568L) water tank
- Water pump
- Variable volume (0 to full) pump output
- Double hydraulic circuit with accumulator
- Proximity sensors in hydraulic cylinders
- Hard-chromed concrete cylinders
- Long lasting fabric-reinforced piston cups
- Proven reliable S-Valve with splined shaft
- Twin shifting ball and socket cylinders
- Centralized hopper-mounted grease system
- Hydraulic remixer/agitator
- Fully enclosed weatherproof control panel with color display of pump information
- Multi-Function remote control with 100 ft (30m) cable
- High quality paint finish

## **VSP 60HP Specifications**

Dimensions		
Fill height	46.3"	(1,175mm)
Deck height	44.5″	(1,130mm)
Deck length	12.5	(3.81m)
Height	80.3	(2,040mm)
Width	96.5"	(2,450mm)
Length	29′	(8.8m)

Capacities		
Hopper	9.5 ft <sup>3</sup>	270L
Hydraulic tank	45 gal	170L
Water tank	150 gal	570L

Performance		
Output Vol	56 yd³/hr	43m³/hr
Output Press	1,450 psi	100 bar
Strokes/min	44	

Major Parts	
Hy-cyl	110 x 63 R mm
Del-cyl	150 x 1000mm
S-tube	S1512
Outlet	5″ HD

Chassis			
Mfr	Ram 5500	Ram 5500 Regular Cab 4x4	
Engine	6.7L	6.7L Cummins Diesel	
Power	325 hp	242kW	
Torque	750 lb-ft	1,016Nm	
Transmission	Automatic 6-speed		
Fuel tank	45 gal	170L	
WB	204″	5,180mm	
CA	120″	3,050mm	
Max GVWR	19,500 lb	8,845kg	
Max GAWR Front	7,250 lb	3,288kg	
Max GAWR Rear	13,500 lb	6,123kg	





Putzmeister America, Inc. 1733 90th Street Sturtevant. WI 53177 USA Phone Toll-free Fax (262) 886-3200 (800) 884-7210 (262) 884-6338